

VIDEO SCAN CONVERTER , HALF-RACKMOUNT

TECHNICAL SPECIFICATIONS

FEATURES

- Provides for conversion between High Definition and Standard Definition video formats
- Advanced scaling algorithm, de-interlacing, and aspect ratio conversion for optimal video quality
- HD/SD-SDI/DVI/HDMI/VGA/Composite Analog Inputs and Outputs



The VSC/890H Video Scan Converter is a commercial/industrial unit that provides video format conversion. The VSC/890H accepts SMPTE, graphics, or analog composite video formats, at various resolutions and frame rates, and converts it to a format that is compatible with legacy and new system displays, recorders, and/or transmission equipment. Typical applications are converting the graphics output of an MPD to RS-170 for on-board recording or converting an RS-343 HUD output to XGA for display on a standard video display. The VSC/890R supports HD/SD-SDI (SMPTE), DVI/HDMI, VGA, and composite input and output formats.

High-quality motion adaptive de-interlacing and aspect ratio conversion, in combination with an advanced scaling algorithm, ensures near-optimum-quality video output. The scaling is implemented using multi-tap FIR filtering and advanced interpolation, both horizontally and vertically.

The VSC/890H is a half-rackmount chassis available in AC and DC power. All I/O connections are located on the rear panel of the unit. The unit is easily configured via the front panel and the serial or Ethernet ports. Rackmount adaptor kits are available to mounting for one or two units in a 1RU rack space.

A division of Delta Information Systems, Inc.

747 Dresher Road, Suite 125 • Horsham, PA 19044-2247 • Tel (215) 657-5270 • Fax (215) 657-5273 • www.deltadigitalvideo.com

VIDEO SCAN CONVERTER , HALF-RACKMOUNT

VIDEO INPUT/OUTPUT

Ports	Five
Format	Composite/HD-SDI/DVI/HDMI/VGA
Format	NTSC/PAL; RS-343; SMPTE-259/292; DVI-D/HDMI; VGA, RG _s B
Connector	BNC/DVI

CONTROL/BIT

Ports	Two
Format	RS-232/TCP-IP
Protocol	Delta 's 3-character mnemonics
Connector	DB-9/RJ-45

VIDEO SCALING

Algorithm	Multi-tap Scaling w/ H & V Interpolation
Format	Interlaced & Progressive
Resolutions	480i/576i/875i/720p/1080i/ 1080p/640x480/800x600/1024x768/ 1280x1024
Frame Rate	29.97/25/30/50/59.94/60/75

ENVIRONMENTAL


Temp-Operating	-20°C to +60°C
Temp-Non-operational	-40°C to +85°C

POWER

Volts	120-240VAC, 50-60Hz
Watts	15W
Connector	EIA-320

SIZE / WEIGHT

Chassis	1.75 "H x 5.4 "W x 7.5 "D / 3.0lbs.
---------	-------------------------------------



©2012 Delta Information Systems, Inc.
All rights reserved. Revision 101730
Subject to change without notice.

A division of Delta Information Systems, Inc.

747 Dresher Road, Suite 125 • Horsham, PA 19044-2247 • Tel (215) 657-5270 • Fax (215) 657-5273 • www.deltadigitalvideo.com



Instrumentation Devices Srl

Via Acquanera 29 - 22100 COMO (Italy)
ph +39 031 525 391- fax +39 031 507 984

info@instrumentation.it - www.instrumentation.it